

## Concrete floor channels, covers and edge protections

### **Scope**

This standard describes concrete floor channels in the width range of 300–900 and is primarily intended as an aid for the purchaser for consultancy assignments for the design of channels. For floor channels of smaller dimensions, refer to suppliers of prefabricated structures in stainless steel plate or polyester concrete.

### **Changes since the previous edition**

This edition differs from the previous one in that:

- Chapter 6.4 – “Anchoring of edge protection” now refers to [SSG 6563E – Edge protection by angle sections. Instructions for construction](#).
- Former chapter 6.3 – “Steel grid cover, Edge protection” has been removed.
- Fig. 4 – “Stainless channel type 1.”, Fig. 5 – “Stainless channel type 1, detail 1.”, Fig. 6 – “Stainless channel, type 2.” and Fig. 7 – “Stainless channel, type 3.” has been modified regarding steel material.

### **Contents**

<b>1</b>	<b>Related documents</b>	2
<b>2</b>	<b>Designation</b>	2
2.1	Example	2
<b>3</b>	<b>Surface coating</b>	2
<b>4</b>	<b>Width, depth</b>	2
<b>5</b>	<b>Channel types, implementation</b>	3
5.1	Haunched channel	3
5.2	Straight channel	4
5.3	Lined channel	4
5.4	Stainless channel type 1, 2 and 3	5
5.4.1	Type 1	5
5.4.2	Type 2	6
5.4.3	Type 3	7
<b>6</b>	<b>Covering class</b>	8
6.1	Execution	8
6.2	Width	8
6.3	Concrete lid	9
6.3.1	Channel width 300	9
6.3.2	Channel width 400	9
6.3.3	Channel width 600	10
6.3.4	Channel width 600	10
6.3.5	Channel width 900	10
6.3.6	Channel width 900	11
6.4	Anchoring of edge protection	11
<b>7</b>	<b>References</b>	11
<b>Appendix 1: Process criteria</b>		