

## Seamless floor coatings of plastic-based compound in the pulp and paper industry

### Introduction

[Information within brackets in this document refers to local regulations]

This report contains instructions on the use of seamless floor coatings of plastic-based compound in the pulp and paper industry.

Håkan Forsberg, Golvanalys Sverige AB and SVEFF (The Swedish Paint and Printing Ink Makers Association) has assisted in the work of producing Version 2 of the SSG 1906 Report.

### Contents

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| <b>1 General</b>                                                       | <b>3</b>  |
| <b>2 Coating types</b>                                                 | <b>4</b>  |
| 2.1 Dust binding, impregnation and sealing                             | 4         |
| 2.2 Painting                                                           | 4         |
| 2.2.1 Acrylate-based paints                                            | 4         |
| 2.2.2 Epoxy-based paints                                               | 4         |
| 2.2.2.1 Water-borne epoxy paints                                       | 4         |
| 2.2.2.2 Epoxy paints containing solvents                               | 4         |
| 2.3 Thin-film coatings < 1 mm                                          | 5         |
| 2.4 Compound coatings                                                  | 5         |
| 2.4.1 General                                                          | 5         |
| 2.4.1.1 Acrylic coatings                                               | 6         |
| 2.4.1.2 Epoxy coatings                                                 | 7         |
| 2.4.1.3 Polyurethane (PU) coatings                                     | 8         |
| 2.4.1.4 Vinyl ester and polyester coatings                             | 8         |
| 2.4.2 Coating methodology                                              | 9         |
| 2.4.2.1 Method 1. Self-levelling coating (solid coating)               | 9         |
| 2.4.2.2 Method 2. Sprinkled coating Slurry method (structural coating) | 10        |
| 2.4.2.3 Method 3. Steel-trowelled coating (unsaturated plastic mix)    | 10        |
| 2.4.2.4 Method 4: Steel-trowelled coating (saturated plastic mix)      | 11        |
| 2.4.2.5 Method 5: Compact coating                                      | 11        |
| 2.4.3 Binders and coating method                                       | 12        |
| 2.4.4 Functional requirements                                          | 12        |
| 2.4.4.1 Anti-slip protection                                           | 13        |
| 2.4.4.2 Dry environments                                               | 13        |
| 2.4.4.3 Wet environments                                               | 14        |
| 2.4.4.4 Thermal loading                                                | 14        |
| 2.4.4.5 Chemical loading                                               | 15        |
| 2.4.4.6 ESD floor; antistatic and electrostatic-discharge coatings     | 16        |
| <b>3 Application of coatings</b>                                       | <b>17</b> |
| 3.1 Self-levelling coatings                                            | 17        |
| 3.2 Sprinkled coatings                                                 | 17        |
| 3.3 Steel-trowelled coatings, (unsaturated plastic mix)                | 18        |
| 3.4 Steel-trowelled coatings (saturated plastic mix)                   | 18        |
| 3.5 Compacted coatings                                                 | 19        |
| 3.6 Levelling with plastic mix                                         | 20        |
| <b>4 Advantages and disadvantages of different application methods</b> | <b>21</b> |
| 4.1 Self-levelling coatings                                            | 21        |
| 4.2 Sprinkled coatings                                                 | 21        |
| 4.3 Steel-trowelled coatings, (unsaturated plastic mix)                | 21        |
| 4.4 Steel-trowelled coatings (saturated plastic mix)                   | 22        |

# Seamless floor coatings of plastic-based compound in the pulp and paper industry

## Report

SSG 1906E

Date  
2009-10-01

Edition  
2

Designation Page  
TKB/TKY 2 (31)

---

|                                                                                                            |           |
|------------------------------------------------------------------------------------------------------------|-----------|
| 4.5 Compacted coatings . . . . .                                                                           | 22        |
| <b>5 Substrate . . . . .</b>                                                                               | <b>23</b> |
| 5.1 Functional requirements . . . . .                                                                      | 23        |
| 5.1.1 Concrete . . . . .                                                                                   | 23        |
| 5.1.2 Bituminous products . . . . .                                                                        | 24        |
| 5.1.3 Levelling products . . . . .                                                                         | 24        |
| 5.1.3.1 Cement-based . . . . .                                                                             | 24        |
| 5.1.3.2 Plastic-based . . . . .                                                                            | 24        |
| 5.1.4 Clinker and other ceramic materials . . . . .                                                        | 24        |
| 5.2 Preparation . . . . .                                                                                  | 24        |
| 5.2.1 Degreasing . . . . .                                                                                 | 25        |
| 5.2.2 Milling . . . . .                                                                                    | 25        |
| 5.2.3 Blasting . . . . .                                                                                   | 25        |
| 5.2.4 Acid pickling . . . . .                                                                              | 25        |
| 5.2.5 Flame cleaning . . . . .                                                                             | 26        |
| 5.2.6 Grinding . . . . .                                                                                   | 26        |
| 5.2.7 Priming . . . . .                                                                                    | 26        |
| <b>6 Damage . . . . .</b>                                                                                  | <b>27</b> |
| 6.1 Direct physical damage of limited extent . . . . .                                                     | 27        |
| 6.2 Damage due to ageing or material fatigue . . . . .                                                     | 27        |
| 6.3 Damage attributable to thermal shock . . . . .                                                         | 27        |
| 6.4 Chemical attack . . . . .                                                                              | 27        |
| 6.5 Tyre marks . . . . .                                                                                   | 28        |
| <b>7 Factors which may help to prolong the life of floor compounds . . . .</b>                             | <b>28</b> |
| <b>8 Inspection . . . . .</b>                                                                              | <b>29</b> |
| 8.1 Prior to application . . . . .                                                                         | 29        |
| 8.2 During application . . . . .                                                                           | 29        |
| 8.3 On completion of work . . . . .                                                                        | 30        |
| <b>9 Guarantee conditions . . . . .</b>                                                                    | <b>31</b> |
| <br><b>Appendix 1 Standard report form for inspection of floor with plastic-based compound coating</b>     |           |
| <br><b>Appendix 2 Enquiry documentation prior to work with floor with plastic-based compound coating</b>   |           |
| <br><b>Appendix 3 Report for assessment of completed work on floor with plastic-based compound coating</b> |           |