Förhandsgranskning / Preview

SSG®

Report **SSG 1906E**

Date	Edition	Designation	Page
2009-10-01	2	TKB/TKY	1 (31)

Seamless floor coatings of plastic-based compound in the pulp and paper industry

Introduction

[Information within brackets in this document refers to local regulations**]**

This report contains instructions on the use of seamless floor coatings of plastic-based compound in the pulp and paper industry.

Håkan Forsberg, Golvanalys Sverige AB and SVEFF (The Swedish Paint and Printing Ink Makers Association) has assisted in the work of producing Version 2 of the SSG 1906 Report.

Contents

1 General . . . 3

2 Coating types . . . 4
2.1 Dust binding, impregnation and sealing . . . 4
2.2 Painting . . . 4
2.2.1 Acrylate-based paints . . . 4
2.2.2 Epoxy-based paints . . . 4
2.2.2.1 Water-borne epoxy paints . . . 4
2.2.2.2 Epoxy paints containing solvents . . . 4
2.3 Thin-film coatings < 1 mm . . . 5
2.4 Compound coatings . . . 5
2.4.1 General . . . 5
2.4.1.1 Acrylic coatings . . . 6
2.4.1.2 Epoxy coatings . . . 7
2.4.1.3 Polyurethane (PU) coatings . . . 8
2.4.1.4 Vinyl ester and polyester coatings . . . 8
2.4.2 Coating methodology . . . 9
2.4.2.1 Method 1. Self-levelling coating (solid coating) . . . 9
2.4.2.2 Method 2.Sprinkled coating Slurry method (structural coating) . . . 10
2.4.2.3 Method 3.Steel-trowelled coating (unsaturated plastic mix) . . . 10
2.4.2.4 Method 4: Steel-trowelled coating (saturated plastic mix) . . . 11
2.4.2.5 Method 5: Compact coating . . . 11
2.4.3 Binders and coating method . . . 12
2.4.4 Functional requirements . . . 12
2.4.4.1 Anti-slip protection . . . 13
2.4.4.2 Dry environments . . . 13
2.4.4.3 Wet environments . . . 14
2.4.4.4 Thermal loading . . . 14
2.4.4.5 Chemical loading . . . 15
2.4.4.6 ESD floor; antistatic and electrostatic-.discharge coatings . . . 16

3 Application of coatings . . . 17
3.1 Self-levelling coatings . . . 17
3.2 Sprinkled coatings . . . 17
3.3 Steel-trowelled coatings, (unsaturated plastic mix) . . . 18
3.4 Steel-trowelled coatings (saturated plastic mix) . . . 18
3.5 Compacted coatings . . . 19
3.6 Levelling with plastic mix . . . 20

4 Advantages and disadvantages of different application methods . . . 21
4.1 Self-levelling coatings . . . 21
4.2 Sprinkled coatings . . . 21
4.3 Steel-trowelled coatings, (unsaturated plastic mix) . . . 21
4.4 Steel-trowelled coatings (saturated plastic mix.) . . . 22

Not to be reprinted without permission

Förhandsgranskning / Preview

4.5 Compacted coatings 22

5 Substrate 23
5.1 Functional requirements. 23
5.1.1 Concrete 23
5.1.2 Bituminous products 24
5.1.3 Levelling products 24
5.1.3.1 Cement-based 24
5.1.3.2 Plastic-based 24
5.1.4 Clinker and other ceramic materials 24
5.2 Preparation. 24
5.2.1 Degreasing 25
5.2.2 Milling 25
5.2.3 Blasting 25
5.2.4 Acid pickling 25
5.2.5 Flame cleaning 26
5.2.6 Grinding. 26
5.2.7 Priming 26

6 Damage 27
6.1 Direct physical damage of limited extent 27
6.2 Damage due to ageing or material fatigue. 27
6.3 Damage attributable to thermal shock 27
6.4 Chemical attack 27
6.5 Tyre marks 28

7 Factors which may help to prolong the life of floor compounds 28

8 Inspection 29
8.1 Prior to application 29
8.2 During application 29
8.3 On completion of work 30

9 Guarantee conditions 31

Appendix 1 Standard report form for inspection of floor with plastic-based compound coating

Appendix 2 Enquiry documentation prior to work with floor with plastic-based compound coating

Appendix 3 Report for assessment of completed work on floor with plastic-based compound coating