



STANDARD SOLUTIONS GROUP

**SSG 7054E**Date  
2020-04-29Edition  
2Designation  
TKR, RUPage  
1 (3)

## Pipe support elements – spacer for type 8 when pre-tensioning springs

### Scope

The spacer in accordance with this standard is used for type 8 in [SSG 7005E](#) when pre-tensioned springs are used. The spacer is mounted between beam, [SSG 7030E](#) and cup washer, [SSG 7052](#).

### Changes since the previous edition

This edition differs from the previous edition in that:

- The standard has been updated in accordance with the current template for SSG standards.

### Contents

<b>1</b>	<b>Related documents</b>	1
<b>2</b>	<b>Designation</b>	1
2.1	Example	1
<b>3</b>	<b>Requirements</b>	1
3.1	General	1
3.1.1	Materials	1
3.1.2	Surface treatment	1
3.2	Dimensions	2
<b>4</b>	<b>References</b>	3

**1 Related documents** [SSG 7005E](#) – *Anchorage and supports for pipelines – types.*

**2 Designation** Washer SSG 7054 - No.

**2.1 Example** Washer SSG 7054 - 1

### 3 Requirements

#### 3.1 General

**3.1.1 Materials** S235JRG2 according to SS-EN 10025 (SS steel 1312).

**3.1.2 Surface treatment** Hot dip galvanized in accordance with SS-EN ISO 1461.