

Pipe support elements – axial stop

Information within brackets ([...]) in this document refers to local regulations.

Scope

This standard provides recommendations for axial stops, which are used for guides made in accordance with [SSG 7005E](#) – Type 16.

Supports exposed to axial loads should be fitted with stop lugs in accordance with [SSG 7100E](#).

Stop lugs shall be available for the types 16A–16D.

Changes since the previous edition

This edition differs from the previous edition in that:

- Axial forces have been added to tables 3 and 4.
- The standard has been updated in accordance with the current template for SSG standards.

Contents

| | | |
|----------|--|---|
| 1 | Related documents | 1 |
| 2 | Designation | 2 |
| | 2.1 Example | 2 |
| 3 | Requirements | 2 |
| | 3.1 General | 2 |
| | 3.1.1 Description | 2 |
| | 3.1.2 Materials and strength | 2 |
| | 3.1.3 Surface treatment | 2 |
| | 3.1.4 Manufacturing requirements | 2 |
| | 3.2 Dimensions | 3 |
| | 3.2.1 Types A and B | 3 |
| | 3.2.2 Types C and D | 4 |
| 4 | References | 6 |

1 Related documents [SSG 7000E](#) – *Anchorage and supports – design recommendations for pipelines*

[SSG 7005E](#) – *Anchorage and supports for pipelines – types*

[SSG 7100E](#) – *Pipe support elements – stop lugs*

[SSG 7149E](#) – *Pipe support elements – sliding shoe for uninsulated, protective insulated and insulated pipelines with a maximum of 80 mm insulation thickness*

[SSG 7151E](#) – *Pipe support elements – sliding shoe for insulated pipelines.*