



## Pipe support elements – axial stop

Information within brackets ([...]) in this document refers to local regulations.

### Scope

This standard provides recommendations for axial stops, which are used for guides made in accordance with [SSG 7005E](#) – Type 16.

Supports exposed to axial loads should be fitted with stop lugs in accordance with [SSG 7100E](#).

Stop lugs shall be available for the types 16A–16D.

### Changes since the previous edition

This edition differs from the previous edition in that:

- Axial forces have been added to tables 3 and 4.
- The standard has been updated in accordance with the current template for SSG standards.

### Contents

<b>1</b>	<b>Related documents</b>	1
<b>2</b>	<b>Designation</b>	2
2.1	Example	2
<b>3</b>	<b>Requirements</b>	2
3.1	General	2
3.1.1	Description	2
3.1.2	Materials and strength	2
3.1.3	Surface treatment	2
3.1.4	Manufacturing requirements	2
3.2	Dimensions	3
3.2.1	Types A and B	3
3.2.2	Types C and D	4
<b>4</b>	<b>References</b>	6

- 1 Related documents** [SSG 7000E](#) – Anchorages and supports – design recommendations for pipelines
- [SSG 7005E](#) – Anchorages and supports for pipelines – types
- [SSG 7100E](#) – Pipe support elements – stop lugs
- [SSG 7149E](#) – Pipe support elements – sliding shoe for uninsulated, protective insulated and insulated pipelines with a maximum of 80 mm insulation thickness
- [SSG 7151E](#) – Pipe support elements – sliding shoe for insulated pipelines.