

## Pipe support elements – bottom part of flexible supports

Information within brackets ([...]) in this document refers to local regulations.

### Scope

This standard provides recommendations for bottom parts, which are used as flexible supports made in accordance with [SSG 7005E](#) – Type 33.

### Changes since the previous edition

This edition differs from the previous edition in that:

- The measurement settings are changed in sections “3.2” by H in “Fig. 1”.
- The standard has been updated in accordance with the current template for SSG standards.

### Contents

<b>1</b>	<b>Related documents</b> . . . . .	1
<b>2</b>	<b>Designation</b> . . . . .	1
2.1	Example . . . . .	1
<b>3</b>	<b>Requirements</b> . . . . .	2
3.1	General . . . . .	2
3.1.1	Description . . . . .	2
3.1.2	Materials . . . . .	2
3.1.3	Surface treatment . . . . .	2
3.1.4	Manufacturing requirements . . . . .	2
3.2	Dimensions . . . . .	2
<b>4</b>	<b>References</b> . . . . .	5

- 1 Related documents** [SSG 7000E](#) – *Anchorage and supports – design recommendations for pipelines*  
[SSG 7005E](#) – *Anchorage and supports for pipelines – types*  
[SSG 7075E](#) – *Pipe support elements – pipe clamp of steel – split type.*

### 2 Designation

**Bottom part SSG 7175 - D<sub>k</sub> - (H - T)<sup>1)</sup>**

#### 2.1 Example

**Bottom part SSG 7175 - D<sub>k</sub> 43 - H 600 - T 6**

Maximum vertical load for buckling, refer to table page 3.

<sup>1)</sup> Measurements T and H are calculated on a case-by-case basis.