



PED – pipe class MSS40A Metric dimension series, PN 40, Material 1.4307, z=0,7

Orientation

This edition differs from previous by metric dimensions has been introduced to DN 15-50.

Welding ring with collar according to SSG 7370E has been replaced by welding ring with collar according to SS-EN 1092-1:2007, type 35M.

Loose flange according to SS-EN 1092-1, type 02 has been replaced with SS-EN 1092-1:2007, type 02M.

EU Directive 97/23/EC, which in English is known as the Pressure Equipment Directive - PED was adopted by the European Parliament in May 1997.

From 29 May 2002, EU Directive PED 97/23/EC became compulsory throughout the European Union. The European harmonised EN 13480 standard is a standard which complies with the requirements of EU Directive PED 97/23/EC of May 1997. The Swedish Work Environment Authority implemented this EU Directive in Sweden on 31 May 2002 in accordance with regulation AFS 1999:4 entitled "Pressure equipment".

This Pipe Classes standard has been verified and approved against the requirements of SS-EN 13480-3:2002 by the certified body (AO) 0409 Inspecta Sweden AB, certificate no. 09-744845-00.

This standard describes pipe components with metric dimensions, ID, pressure class PN 40. The standard complies with the values for the maximum permitted pressure (P_c) and temperature (T_c) for pressure class PN 40 according to the harmonised European flange standard SS-EN 1092-1:2001, table 17, material group 14E0.

For a list of SSG PED pipe classes, see SSG 7829E

NB!

Component calculations in the pipe class are based on material 1.4307 as per SS-EN standard which is included in material group 8.1 according to CR ISO 15608 (see also SS-EN 13480-2).

This standard, SSG 7834E, may also be applied to other materials in material group 8.1 according to CR ISO 15608 of equal or superior strength values.

If a material of inferior strength value is chosen, the components may NOT be used in accordance with the standard.

Contents

1 List of standards	2
2 Components list	3
3 T table (including welding requirements, see note page 5)	.5